



STANFORD UNIVERSITY  
W.W. HANSEN EXPERIMENTAL PHYSICS LABORATORY  
GRAVITY PROBE B, RELATIVITY GYROSCOPE EXPERIMENT  
STANFORD, CALIFORNIA 94305-4085

## **(PTP) PAYLOAD MAGNETOMETER TEMPORARY INSTALLATION**

### **GP-B PAYLOAD VERIFICATION TEST II OPERATIONS ORDER**

**P0852 Rev -**  
31 May, 2001

PREPARED \_\_\_\_\_  
W. Bencze Date

APPROVED \_\_\_\_\_  
K. Pearce, Systems Test Engr. Date

APPROVED \_\_\_\_\_  
W. Bencze, Test Director Date

APPROVED \_\_\_\_\_  
D. Ross, Quality Assurance Date

APPROVED \_\_\_\_\_  
R. Brumley, Payload Technical Mgr. Date

**REVISION RECORD**

REVISION	ECO	PAGES	DATE

## 1. SCOPE

This procedure provides authority to temporarily connect the payload magnetometers to the flight ECU in the Fist-Ops lab to be used during Payload Verification II Phase B.

### NOTE

**Flight hardware; protect parts and assemblies to prevent magnetic contamination and physical damage.**

## 2. REFERENCE DOCUMENTS

### 2.1. Procedures

Not applicable

### 2.2. Drawings

8A02105                      Payload Cable Interconnection Diagram

### 2.3. FIGURES

Not applicable

### 2.4. SUPPORTING DOCUMENTATION

GP-B Magnetic Control Plan, LMMS-5835031

GP-B (FIST) Preliminary Hazards Analysis, LMMS-F314446

GP-B (FIST) Safety Plan, LMMS- F314447

FIST Emergency Procedures SU/GP-B P0141

SRE GSE Equipment Test Procedure P0843

### 3. GENERAL REQUIREMENTS

#### 3.1 Quality Assurance

Integration shall be conducted on a formal basis to approved and released procedures. The QA program office shall be notified of the start of this procedure. A Quality Assurance Representative, designated by D. Ross shall be present during the procedure and shall review any discrepancies noted and approve their disposition. Upon completion of this procedure, the QA Program Engineer, D. Ross or her designate, nominally R. Leese, will certify her concurrence that the effort was performed and accomplished in accordance with the prescribed instructions by signing and dating in the designated place(s) in this document. Discrepancies will be recorded in a D-log or as a DR per Quality Plan P0108.

#### 3.2 Red-line Authority

Authority to red-line (make minor changes during execution) this procedure is given solely to the Test Director or his designate and shall be approved by the QA Representative. Additionally, approval by the Payload Technical Manager shall be required, if in the judgment of the Test Director or QA Representative, experiment functionality may be affected.

#### 3.3 Personnel

The following personnel are qualified to perform this procedure:

- William Benzce
- Lo Van Ho
- Scott Smader
- Rick Bevan
- Other: \_\_\_\_\_ QA approval \_\_\_\_\_

See section 3.1 for details on which Quality Assurance personnel are required to be notified and/or witness this procedure.

#### 3.4 Safety

**In case of any injuries obtain medical treatment at:**

Stanford University **Call 9-911**

#### 4. CONFIGURATION REQUIREMENTS:

4.1 SMD mounted in SMD test stand with the work platforms and scaffolding attached.

#### 5. HARDWARE REQUIREMENTS

The Dewar, SRE and accompanying build hardware are very delicate. Be sure to handle them with care so that they do not become damaged.

**NOTE**

**Take all necessary precautions not to let anything physically damage the SRE and Science Mission Dewar or particulate onto its surfaces.**

##### 5.1 Hardware Required:

- Qt. 2 Payload Magnetometer "Left" PN: APS 900-1130-L (SN 1,2)
- Qt. 2 Payload Magnetometer "Right" PN" APS 900-1130-R (SN 3,4)
- Qt. AR Cable ties
- Qt. 4 Cable tie blocks.
- Qt. 5 ESD mat and ground wire.
- Qt. AR Hand tools (Allen wrenches, screw drivers, etc.)

#### 6. OPERATIONS:

Operator \_\_\_\_\_.

Date Initiated \_\_\_\_\_.

Time Initiated \_\_\_\_\_.

#### 7. NOTIFICATION

##### 7.1 Safety Notification

Safety shall be notified 24 hours in advance prior to the start of any work performed. Record who was contacted, the date, and time below.

Contact: \_\_\_\_\_  
Date and Time: \_\_\_\_\_

**7.2 Quality Assurance Notification**

The Test Director is to notify the Quality Engineer 24 hours in advance prior to the start of any work performed. Record who was contacted, the date, and time below.

Contact: \_\_\_\_\_  
Date and Time: \_\_\_\_\_

**7.3 Government Notification**

Quality Engineer to notify Government Representative 24 hours in advance prior to the start of any work performed. Record who was contacted, the date, and time below.

Contact: \_\_\_\_\_  
Date and Time: \_\_\_\_\_


## 8. INSTALLING THE SRE UNIT AND CABLES

### 8.1 Mounting the Magnetometer Units

#### **CAUTION**

**The Magnetometer Units are ESD Sensitive. Use appropriate ESD protection when handling the unit or installing associated cables.**

- 8.1.1 Locate table with ESD mat and cable tie blocks attached (Figure 1) Insure ESD mat is properly grounded to Dewar ground point.



P0852-1

Figure 1 – Layout of Magnetometer Test Stand

- 8.1.2 Affix ends of cables W314 and W315 to tie-down blocks as shown in Figure 1 using cable ties. Connector end of cable should have sufficient slack to enable it to mate to the magnetometer assemblies..
- 8.1.3 Connect each magnetometer to the end of its respective cable. Prior to installing each cable, inspect the cable's connectors and mating connectors for bent or misaligned pins or sockets. If any contacts are discrepant, do not install the cable and notify Quality Assurance in order to document the discrepancy. Once mated, finger tighten screws in connector backshell, and set each magnetometer on ESD mat. No further securing of the magnetometers is required.
- 8.1.4 Verify that all the cables are installed in their proper locations and their fasteners are hand tight.
- 8.1.5 Quality Assurance to witness connection

QA Witness \_\_\_\_\_

**Approval of Section 8.1**

Approved: \_\_\_\_\_ Date: \_\_\_\_\_  
Integration Engineer

Discrepancies if any:

Approved: \_\_\_\_\_ Date: \_\_\_\_\_  
QA Representative

Approved: \_\_\_\_\_ Date: \_\_\_\_\_  
Integration Manager



**8.2 Connecting Magnetometer cables to ECU**

**CAUTION**

**The Magnetometer Units and ECU are ESD Sensitive. Use appropriate ESD protection when handling the unit or installing associated cables.**

- 8.2.1 Confirm that the ECU is powered **OFF**.
- 8.2.2 Once the Magnetometers are installed on the test stand, connect two cables to the ECU per 8A02105 Prior to installing each cable, inspect the cable’s connectors and mating connectors for bent or misaligned pins or sockets. If any contacts are discrepant, do not install the cable and notify Quality Assurance in order to document the discrepancy.
 

W314	8A01548-101
W315	8A01549-101
- 8.2.3 Verify that all the cables are installed in their proper locations and their fasteners are hand tight.

**Approval of Section 8.2**

Approved: \_\_\_\_\_ Date: \_\_\_\_\_  
Integration Engineer

Discrepancies if any:

Approved: \_\_\_\_\_ Date: \_\_\_\_\_  
QA Representative

Approved: \_\_\_\_\_ Date: \_\_\_\_\_  
Integration Manager

**9. PROCEDURE COMPLETED**

The results obtained in the performance of this procedure are acceptable:

Test Engineer \_\_\_\_\_ Date \_\_\_\_\_

Discrepancies if any:

The information obtained under this assembly and test procedure is as represented and the documentation is complete and correct:

Integration Manager \_\_\_\_\_ Date \_\_\_\_\_

QA Representative \_\_\_\_\_ Date \_\_\_\_\_

Quality Assurance Manager \_\_\_\_\_ Date \_\_\_\_\_